

PolyJet Material/Printer Reference

Rigid Opaque

Material	Objet30 Pro™	Objet30 Prime™	Stratasys J4100™	Stratasys J735™ ¹ /J750™	Stratasys J850™ Core	Stratasys J850™ Pro/Prime/J826™ Prime	Stratasys J55™ Prime	Stratasys J35™ Pro
VeroWhitePlus™ (RGD835)	●	●	○	○	○	○	○	○
VeroBlackPlus™ (RGD875)	●	●	●	●	○	●	●	○
VeroBlue™ (RGD840)	●	●	●	●	○	○	○	○
VeroGray™ (RGD850)	●	●	●	●	○	○	○	○
VeroCyan™ (RGD843)	○	○	○	●	○	● ³	○	○
VeroMagenta™ (RGD851)	○	○	○	●	○	● ³	○	○
VeroYellow™ (RGD836)	○	○	○	●	○	● ³	○	○
Vero PureWhite™ (RGD837)	○	○	●	●	○	●	●	○
DraftGrey™ (RGD750)	● ²	● ²	○	○	●	●	●	●
VeroUltra™ White (RGD825)	○	○	○	●	●	●	○	○
VeroUltra Black (RGD865)	○	○	○	●	●	●	○	○
VeroUltra WhiteS (RGD824)	○	○	○	○	○	○	●	●
VeroUltra BlackS (RGD864)	○	○	○	○	○	○	●	●

Rigid Transparent

Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735 ¹ /J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
VeroCyanV™ (RGD845)	○	○	● ⁴	●	○	● ³	●	○
VeroMagentaV™ (RGD852)	○	○	● ⁴	●	○	● ³	●	○
VeroYellowV™ (RGD838)	○	○	● ⁴	●	○	● ³	●	○
RGD720™ (General Purpose Transparent)	○	●	○	●	○	○	○	○
VeroClear™ (RGD810)	●	●	●	●	●	●	●	○
VeroUltra Clear (RGD820)	○	○	●	●	●	●	○	○
VeroUltra ClearS (RGD821)	○	○	○	○	○	○	●	●
Vero™ContactClear (CTT610)	○	○	○	○	○	●	●	●

¹ Subject to regional availability

² Available on select V5 and select V3 systems

³ Not available with J850 Pro

⁴ Sold as MTO – Make To Order only



PolyJet Material/Printer Reference

Simulated Rubber

Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735 ¹ /J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
TangoGray™ (FLX950)	○	●	○	○	○	○	○	○
TangoBlack™ (FLX973)	○	●	○	○	○	○	○	○
TangoPlus™ (FLX930)	○	○	○	●	○	○	○	○
TangoBlackPlus™ (FLX980)	○	○	○	●	○	○	○	○
Agilus30™ Black (FLX985)	○	○	●	●	●	●	○	○
Agilus30 White (FLX945)	○	○	○	●	●	●	○	○
Agilus30 (Transparent) (FLX935)	○	○	●	●	●	●	○	○
Agilus30 Cyan (FLX941)	○	○	○	●	○	● ²	○	○
Agilus30 Magenta (FLX951)	○	○	○	●	○	● ²	○	○
Agilus30 Yellow (FLX931)	○	○	○	●	○	● ²	○	○
Elastico™ Black	○	○	○	○	○	○	●	●
Elastico Clear	○	○	○	○	○	○	●	●

Simulated Polypropylene

Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735 ¹ /J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
Durus™ (RGD430)	●	●	○	○	○	○	○	○
Rigur™ (RGD450)	●	●	○	○	○	○	○	○

¹ Subject to regional availability

² Not available with J850 Pro

¹ Subject to regional availability

² Not available with J850 Pro



PolyJet Material/Printer Reference

Simulated Engineering Plastics

Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735/J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
ToughONE™ White Pure	○	○	○	○	●	●	○	○
ToughONE White Reinforced (with RGD531S)	○	○	○	○	●	●	○	○
ToughONE Black Pure	○	○	○	○	●	● ¹	○	○
ToughONE Black Reinforced (with RGD531S)	○	○	○	○	●	● ¹	○	○
ToughONE™ WhiteS Pure	○	○	○	○	○	○	●	●
ToughONE™ WhiteS Reinforced (with RGD531S)	○	○	○	○	○	○	●	●
Digital ABS Plus Ivory (RGD515 Plus & RGD531)	○	○	●	●	●	●	●	●
RGD525™ (High Temperature)	●	●	○	○	○	○	○	○

Medical & Dental

Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735/750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
VeroDent™ (MED670)	○	○	○	○	○	○	○	○
VeroGlaze™ (MED620)	○	● ²	○	● ³	○	○	○	○
Biocompatible Clear (MED610)	○	●	○	●	○	○	○	○
Digital ABS Plus Biocompatible (MED515+DABS, IV and MED531DABS, IV)	○	○	○	● ²	○	○	○	○
Rigid Ivory Biocompatible (MED615RGD, IV)	○	○	○	● ²	○	○	○	○
TissueMatrix™ (MED310)	○	○	○	○	○	○	○	○
GelMatrix™ (FLG110)	○	○	○	○	○	○	○	○
BoneMatrix™ (RGD516)	○	○	○	○	○	○	○	○
RadioMatrix™ (MED410)	○	○	○	○	○	○	○	○

¹ Not available with J826 Prime

² Available only on J735/J750

³ Available only when printing in J750/J850 (non-DAP) configuration.



PolyJet Material/Printer Reference

Specialty								
Material	Objet30 Pro	Objet30 Prime	Stratasys J4100	Stratasys J735/J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
VeroFlex™ Cyan (RGD891)	○	○	○	●	○	○	○	○
VeroFlex Magenta (RGD892)	○	○	○	●	○	○	○	○
VeroFlex Yellow (RGD893)	○	○	○	●	○	○	○	○
VeroFlex White (RGD894)	○	○	○	●	○	○	○	○
VeroFlex Black (RGD895)	○	○	○	●	○	○	○	○
VeroFlex Clear (RGD896)	○	○	○	●	○	○	○	○
VeroFlexVivid™ Cyan (RGD898)	○	○	○	●	○	○	○	○
VeroFlexVivid Magenta (RGD899)	○	○	○	●	○	○	○	○
VeroFlexVivid Yellow (RGD890)	○	○	○	●	○	○	○	○

Support									
Material	Objet30 Pro	Objet30 Prime	Objet Eden260VS	Stratasys J4100	Stratasys J735/J750	Stratasys J850 Core	Stratasys J850 Pro/Prime/J826 Prime	Stratasys J55 Prime	Stratasys J35 Pro
SUP705™ and SUP705B (Water Jet Removal) ¹	●	●	●	●	●	●	●	○	○
Biocompatible ² with FC630; FC655; MED610; MED620; MED625FLX ² ; MEDDABS+; MED615RGD	●	●	●	●	●	●	●	○	○
SUP706B™ (Soluble Support)	●	●	○	○	●	○	●	○	○
Biocompatible ² with MED610; MED620; MED625FLX; MEDDABS+; MED615RGD ²	●	●	○	○	●	○	●	○	○
SUP707™ (Water Soluble)	○	○	●	○	○	○	○	○	○
SUP710™	○	○	○	○	○	○	○	●	●
WSS™150	○	○	○	○	○	○	○	●	●

¹Available at EMEA and APJ only

²Biocompatibility is system dependent, please refer to the Medical & Dental section above



PolyJet Material/Printer Reference

Packaging Details

Printer	Type	Amount (kg)	Packing
Eden/Connex	Cartridge	3.6 kg	Pack of 1/Pack of 4 ¹
Stratasys J735/J750	Cartridge	3.6 kg	Pack of 1/Pack of 3 ¹
Objet30 Pro/Prime	Cartridge	1 kg	Pack of 2
Stratasys J850 Core	Cartridge	4 kg	Pack of 1
Stratasys J850 Pro/Prime/ J826 Prime	Cartridge	4 kg	Pack of 1
Stratasys J55 Prime	Cartridge	1.1 kg	Pack of 1
Stratasys J35 Pro	Cartridge	1.1 kg	Pack of 1
Stratasys Objet1000 / J4100	Cartridge	18 kg	Pack of 1

¹Not available with J826 Prime

PolyJet Material/Printer Reference

Printer Details

Printer	Maximum Build Size (XYZ)	System Size and Weight	Layer Thickness	Accuracy
Objet30 Pro, Objet30 Prime	294 x 192 x 148.6 mm (11.57 x 7.55 x 5.85 in.)	826 x 600 x 620 mm (32.5 x 23.6 x 24.4 in.); 106 kg (234 lbs.)	Objet30 Pro: 28 microns (0.0011 in.), 16 microns (0.0006 in.) for VeroClear material Objet30 Prime: 28 microns (0.0011 in.) for Tango™ materials; 16 microns (0.0006 in.) for all other materials	0.1 mm (0.0039 in.)
Stratasys J4100	1000 x 800 x 500 mm (39.4 x 31.5 x 19.7 in.)	1960 x 2868 x 2102 mm (77.5 x 113 x 83 in.); 22000 kg (4850 lbs.)	HS: up to 3 base resins, 27 micron (0.001 in.) resolution SHS: single resin, 55 micron (0.002 in.) resolution	Up to 600 microns for full model size (for rigid materials only, depending on geometry, build parameters.)
Stratasys J700/J735/J750	Stratasys J700: 490 x 390 mm (19.3 x 15.35 in.) Stratasys J735: 350 x 350 x 200 mm (13.7 x 13.7 x 7.6 in.) Stratasys J750: 490 x 390 x 200 mm (19.3 x 15.35 x 7.9 in.)	1,400 x 1,260 x 1,100 mm (55.1 x 49.6 x 43.3 in.) 430 kg (948 lbs.) Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)	Stratasys J700: 55 microns (0.0021 in.) Stratasys J735/J750: Horizontal build layers down to 14 microns (.00055 in.) HS mode (28-30 microns)	Stratasys J735/J750: Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm – ±100µ; above 100 mm – ±200µ or ± 0.06% of part length, whichever is greater.
Stratasys J850 Core	490 x 390 x 200 mm (19.3 x 15.35 x 7.9 in.)	1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.) Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs.)	HQ: up to 3 base resins, 14 microns HS: up to 3 base resins, 14 microns	Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm – ±100µ; above 100 mm – ±200µ or ± 0.06% of part length, whichever is greater.
Stratasys J850 Pro/Prime	490 x 390 x 200 mm (19.3 x 15.35 x 7.9 in.)	1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.) Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs.)	HQ: up to 3 base resins, 14 microns HS: up to 6 base resins, 27 microns High Mix: up to 6 base resins, 27 microns SHS?: single resin, 54 microns	Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm – ±100µ; above 100 mm – ±200µ or ± 0.06% of part length, whichever is greater.
J826 Prime	255 x 252 x 200 mm (10 x 9.9 x 7.9 in.)	820 x 1310 x 665 mm (32.28 x 51.57 x 26.18 in.); 234 kg (516 lbs.) Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs.)	HQ: up to 3 base resins, 14 microns HS: up to 6 base resins, 27 microns High Mix: up to 6 base resins, 27 microns SHS?: single resin, 54 microns	Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm – ±100µ; above 100 mm – ±200µ.
Stratasys J55 Prime	Round Print Tray with up to 1,174 cm² (182 in²) Print Height: 190mm* (7.48 in.)*	651 x 661 x 1551 mm (25.63 x 26.02 x 61.06 in.); 228 kg (503 lbs.)	Horizontal build layers down to 18.75 microns (0.0007 in.)	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150µ; above 100 mm – ±0.15% of part length.** Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180µ; above 100 mm – ±0.2% of part length.**
Stratasys J35 Pro	Round Print Tray with up to 1,174 cm² (182 in²) Print Height: 158 mm* (6.22 in.)*	651 x 661 x 774 mm (25.63 x 26.02 x 30.48 in.); 98 kg (216 lbs.)	Horizontal build layers down to 18.75 microns (0.0007 in.)	Deviation from STL dimensions, for 1 Sigma (67%) of models printed with rigid materials, based on size: under 100 mm – ±150µ; above 100 mm – ±0.15% of part length.** Deviation from STL dimensions, for 2 Sigma (95%) of models printed with rigid materials, based on size: under 100 mm – ±180µ; above 100 mm – ±0.2% of part length.**

* The maximal printable height for the J55 Prime is 187 mm (7.36 in.) and the maximal printable model height for the J35 Pro is 155 mm (6.1 in.).

** Measured when ambient temperature is 23 °C and relative humidity is 50%.



alphacam GmbH
Erlenwiesen 16
D-73614 Schorndorf
Tel.: +49 7181 9222-0
info@alphacam.de

alphacam austria GmbH
Handelskai 92, Gate1 / 2. OG / Top A
A-1200 Wien
Tel.: +43 1 3619 600-0
info@alphacam.at

alphacam swiss GmbH
Zürcherstrasse 14
CH-8400 Winterthur
Tel.: +41 52 26207-50
info@alphacam.ch



alphacam.de

.at

.ch

stratasys.com

ISO 9001:2015
Certified



MATERIAL GUIDE
POLYJET

© 2026 Stratasys. All rights reserved. Stratasys, Stratasys Signet logo, PolyJet, Objet30 Pro, Objet30 Prime, Objet Eden260VS, Objet260 Connex1, Objet500 Connex1, J4100, J735, J750, J826, J850, J55, VeroDent, VeroDentPlus, VeroGlaze, TissueMatrix, BoneMatrix, GelMatrix, RadioMatrix, Vero WhitePlus, VeroBlackPlus, VeroBlue, VeroGray, VeroCyan, VeroMagenta, VeroYellow, Vero PureWhite, TangoGray, TangoBlack, TangoPlus, TangoBlackPlus, Agilus30 Black, Agilus30, VeroMagentaV, VeroYellowV, VeroFlexVivid Cyan, VeroFlexVivid Magenta, VeroFlexVivid Yellow, RGD720, VeroClear, VeroUltraClear, Durus, Rigur, ToughONE, Digital ABS Plus, Digital ABS2 Plus, MED610, MED615, MED620, MED625FLX, SUP705, SUP705B, SUP706B, SUP707 and SUP710 are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. MG_PJ_UTIL_Material vs System Matrix_A4_0426a