

# F370CR Composite Printer



The F370<sup>®</sup>CR is a composite-ready 3D printer capable of printing engineering thermoplastics and composite carbon-filled materials. Hardened components and dedicated print heads provide the durability for extended life necessary when printing with carbon-filled plastics. The combination of composite and standard polymers offers the versatility to cover many manufacturing applications with one printer. Hands-free soluble support material enables printing complex geometries and hands-free post-processing.

The F370CR printer has multiple features designed for ease of use and high uptime.

- GrabCAD Print™ and Insight™ software provide a simple workflow and in-depth print process control
- Fully heated build chamber enables consistent print results with multiple infills from sparse to fully dense
- Material bays located in pullout drawers allow for easy accessibility and fast changes
- Auto changeover capability extends print times
- Built-in camera provides visual remote print monitoring
- Power is supplied by standard wall outlets
- Printers are mounted on casters for easy mobility

## F370CR Printer and Material Specifications

<b>System Size/Weight</b>	1626 x 864 x 711 mm (64 x 34 x 28 in.) 500 lbs ( 227 Kg)
<b>Build Tray Dimensions</b>	305 mm x 254 mm x 305 mm (12 x 10 x 12 in.)
<b>Material Delivery</b>	4 material spool bays, 2 for model, 2 for support located in a drawer on the front of the unit
<b>Achievable Accuracy</b>	Parts are produced within an accuracy of +/- .200 mm (.008 in), or +/- .002 mm/mm (.002 in/in), whichever is greater
<b>Network Connectivity</b>	Wired: TCP/IPV6 protocols at 100 Mbps minimum 100 base T, Ethernet protocol, RJ45 connector Wireless-ready: IEEE 802.11n, g, or b; Authentication: WPA2-PSK, 802.1x EAP Encryption: CCMP, TKIP
<b>Operator Attendance</b>	Limited attendance for job start and stop required
<b>Software</b>	GrabCAD Print and Insight software, MTConnect enabled
<b>Operating Environment</b>	Operating: Temperature: 15 – 30 °C (59 – 86 °F), Humidity: 30 – 70% RH Storage: Temperature: 0 – 35 °C (32 – 95 °F), Humidity: 20 – 90% RH
<b>Power Requirements</b>	100-132V/15A or 200–240V/7A. 50/60 Hz
<b>Regulatory Compliance</b>	CE (low-voltage and EMC directive), FCC, EAC, cTUVus, FCC, KC, RoHs, WEEE, Reach, RCM
<b>Operating System</b>	Windows 10 (64 bit only) and Window 11 with a minimum of 4GB RAM (8GB or more recommended)

# F370CR Composite Printer



## Material

Printer

Model Material

F370CR

ABS-M30, ASA, FDM TPU 92A, ABS-ESD7™, PC-ABS™, Diran™ 410MF07, ABS-CF10, FDM Nylon-CF10

## Layer Thickness

Material	0.013 in. (0.330 mm)	0.010 in. (0.254 mm)	0.007 in. (0.178 mm)	0.005 in. (0.127 mm) <sup>3</sup>
ABS-M30	●	●	●	●
ASA	●	●	●	●
PC-ABS	●	●	●	●
ABS-ESD7	○	●	○	○
Diran 410Mf07	●	●	●	○
FDM TPU 92A	○	●	●	○
ABS-CF10 <sup>1</sup>	●	●	●	●
FDM Nylon-CF10 <sup>2</sup>	●	●	●	○

<sup>1</sup> Hardened print head is recommended for extended head life but will also operate using standard F123 and ABS-CF10 print heads.

<sup>2</sup> Dedicated FDM Nylon-CF10 hardened print head required.

<sup>3</sup> F123 T14H Head (123-00603-S) is the only approved head for 0.005in (0.127mm) with ABS-CF10.



alphacam GmbH  
Erlenwiesen 16  
D-73614 Schorndorf  
Tel.: +49 7181 9222-0  
info@alphacam.de

alphacam austria GmbH Handelskai 92,  
Gate1 / 2. OG / Top A A-1200 Wien Tel.:  
+43 1 3619 600-0  
info@alphacam.at

alphacam swiss GmbH  
Zürcherstrasse 14  
CH-8400 Winterthur  
Tel.: +41 52 26207-50  
info@alphacam.ch



alphacam.de  
.at  
.ch

